

**FEATURES**

- Oil lubricated rotary vane vacuum pump Busch, nominal speed 10 m³/h;
- Vacuum level control through high precision absolute-type vacuum sensor, which does not require calibration;
- Maximum vacuum 99,8% (2 millibar);
- 310mm sealing bar with double sealing, easily removable for cleaning;
- Sealing bar lifting system with pistons diameter 80mm;
- Brilliant stainless steel vacuum chamber with constant thickness, easy to clean being free of edges and receptacles;
- Standard inert gas injection with 2 injection nozzles with "Gasplus" system, which allows to reach values up to 90% of inert gas for products extremely sensitive to crushing;
- Standard "Softair" slow air return at the end of the cycle;
- Waterproof control panel, resistant to liquids, humidity, dirt and dust;
- 20 editable user programs;
- 1 cycle for vacuum containers;
- 1 deaeration "chef" cycle (Degas);
- "H2Out" pump oil dehumidification cycle;
- Resettable oil change alarm;
- Menu accessible to technical assistance for parameter adjustment and reading of cycles carried out;
- High-thickness blued PMMA (Plexiglass) lid with polished and rounded edges; opens automatically at the end of the cycle;
- Lowering system of the lid at the end of the work in the rest position by releasing the rear gas spring, which allows to release the tension on the gas spring and on the lid;
- Access for easy maintenance through front opening of the casing;
- Standard "Easy" accessory for external vacuum in embossed bags;
- 2 PE-filling plates for product adjustment and cycle speed up.




SEALING BAR 310mm
VACUUM PUMP 10 m³/h

ABSOLUTE SENSOR CONTROL

ACCESSORIES (NOT INCLUDED)

- Bags for storage, cooking and "cook & chill"; embossed bags;
- Stainless steel cart with castors and shelf;
- Inclined stainless steel plate for liquid packing;
- Stainless steel vacuum containers; suction device.



TECHNICAL DATA

Length of seal L1	mm 310
Nominal pump speed	m³/h 10
Final pressure	mbar 2
Chamber size (FxGxH)	mm 430x343x195
Useful chamber space (N)	mm 380
Chamber depth (L)	mm 135
Chamber volume	lt 19
Power	w 600 (BUSCH)
Electrical voltage/Frequency/Phases	V/Hz 220-240V / 50-60Hz / 1Ph+N+PE
Power cord and plug	2m + IEC / Schuko
Housing materials	Steel inox (AISI304)
Vacuum chamber material	Steel inox (AISI304)
Lid material	PMMA (plexiglas)
Overall dimensions (AxBxC)	mm 415x603x460
Maximum height with open lid (C1)	mm 789
Distance between supports (DxE)	mm 356x425
Weight (with shelves)	kg 46,3
Noise level	dB(A) <70
Environmental operating temperature (min-max)	°C 12-40