



FEATURES

- Oil lubricated 7,1 Acfm (12 m³/h) vacuum pump ;
- Vacuum level control through high precision absolute-type vacuum sensor, which does not require calibration; max vacuum 99,8% (2 millibar);
- 12,2" sealing bar, easily removable for cleaning;
- Hydroformed, brilliant stainless steel vacuum chamber with constant thickness, easy to clean being free of edges and receptacles;
- Standard inert gas injection with 2 injection nozzles with "Gasplus" system, which allows to reach values up to 90% of inert gas for products extremely sensitive to crushing;
- Standard "Softair" slow air return at the end of the cycle;
- Waterproof 5"-TFT touchscreen control panel, protected by scratchresistant tempered glass, resistant to liquids, humidity, dirt and dust;
- 10 editable user programs, with assignable names; 5 settable display languages;
- 9 preset "Chef" cycles for food processing;
- 3 specific preset cycles with inert gas injection;
- 3 specific preset cycles for vacuum containers;
- 2 generic preset cycles for preservation or sous vide cooking;
- 1 programmable deaeration ("Degas") program on eight vacuum phases and eight pause phases;
- "H2Out" pump oil dehumidification cycle;
- Notice of need for oil change, "H2OUT" cycle execution or product cooling need in case of use of insufficiently cooled wet products;
- Menu accessible to technical assistance for parameter adjustment and reading of cycle and maintenance carried out;
- High-thickness trasparent PMMA (Plexiglass) lid with polished and rounded edges; opens automatically at the end of the cycle;
- Lowering system of the lid at the end of the work in the rest position by releasing the rear gas spring, which allows to release the tension on the gas spring and on the lid;
- Access for easy maintenance through front opening of the casing;
- Standard "Easy" accessory for external vacuum in embossed bags;
- 3 PE-filling plates for product adjustment and cycle speed up.



SEALING BAR 12,2 inch


PUMP 7,1 Acfm

ABSOLUTE VACUUM SENSOR



ACCESSORIES (NOT INCLUDED)

- Storage, cooking, and "cook&chill" bags; embossed bags;
- Cart with wheels and stainless steel shelf;
- Stainless steel inclined shelf for liquid packaging;
- Stainless steel vacuum containers and external vacuum suction kit;



TECHNICAL DATA

Sealing bar length L1	inch 12,2
Nominal pump capacity	cfm 7,1
Final pressure	mbar 2
Maximum vacuum chamber dimensions (FxGxH)	inch 17,1x13,5x7,7
Usable vacuum chamber space (N)	inch 15
Tank depth (L)	inch 5,3
Vacuum chamber volume	Usgal 5,02
Rated power	HP 0,5
Rated voltage/Frequency/Phases	V/Hz 110V / 60Hz / 1Ph+N+PE
Power cord and plug	78,7 inch + IEC / Nema 5
Machine body material	Stainless steel (AISI304)
Tank material	Hydroformed stainless steel (AISI304)
Lid material	PMMA (plexiglas)
Maximum footprint (AxBxC)	inch 16,3x23,7x18,1
Maximum height with lid open (C1)	inch 31,1
Distance between supports (DxE)	inch 14x16,7
Weight (with shelves)	lbs 102,1
Noise level	dB(A) <70
Operating temperature (min-max)	°F 53,6-104